



safewaze.com | (P) 704-262-7893 | (F) 704-262-9051
322 Industrial Court, Concord, NC 28025

TECHNICAL DATA SHEET

SW-8008-10-ALU-RBH 10' CLASS A Cable Retractable



Features and Benefits	Safewaze™ retractable lifelines are designed to be used as a single-person fall protection device. The SW-8008-10-ALU-RBH features a mobility-enhancing swivel-top, rugged and durable housing, and a unique braking system that eases shock in the event of a fall.
Length of Cable	10 ft (3.05 m)
Weight of Unit	5.00 lbs (2.27 kg)
Materials	High-strength polymer housing 0.19 in (4.82 mm) Galvanized steel cable Aluminum rebar hook
Hook Ratings	5,000 lbs (2267.96 kg) Tensile Strength 3,600 lbs (1632 kg) Gate Rated
Arresting Force	Max Force <1,800 lbs (816.47 kg); Avg Force <1,350 lbs (612.35 kg)
Maximum Arrest Distance	Arresting distance <24 in (609.60 mm)
Maximum Working Load	420 lbs (190.51 kg)
Cable Tensile Strength	3,700 lbs (1678.29 kg)
Applicable Standards	Meets OSHA 1926.502 - ANSI Z359.14 - ANSI A10.32