

# GRIP-DECK® Hilo THREAD SCREW

## **CERAMIC COATED CORROSION RESISTANCE PHILLIPS DRIVE BUGLE HEAD.**

Weather resistant, ceramic coated Hi-Lo screws. Available in lengths from 1-5/8" up to 6". Use with TRUFAST Walls washers to attach rigid insulation or lath to wood or light gauge steel substrates.





#### **PRODUCT FEATURES**

- Ceramic coating for corrosion resistance.
- Available in bulk (1-5/8" to 6").
- Available in collated (1-5/8" to 6").
- For use on wood or light gauge steel studs.
- Phillips drive with bugle head.

#### **SIZE / GAUGE:**

- 1-5/8" screw, #7 dia. (Bulk or collated)
- 2" screw, #7 dia. (Bulk or collated)
- 2-1/2" screw, #8 dia. (Bulk or collated)
- 3" screw, #8 dia. (Bulk or collated)
- 3-1/2" screw, #10 dia. (Bulk)
- 4" screw, #10 dia. (Bulk)
- 5" screw, #10 dia. (Bulk)
- 6" screw, #10 dia. (Bulk)



### LABOR-SAVING TOOLS AVAILABLE

Use with Grip-Lok<sup>®</sup> Autofeed Fastening System with various nose adaptors for rapid attachment of lath, insulation, building wrap, etc.



TRUFAST

130 Graham St. SW, Grand Rapids, MI 49503 · 616-454-3100 · wallssales@trufast.com ·

www.trufastwalls.com

Bulletin No. TFW-2012